





ITEM	PRODUCT	SPECIFICATION	40A	60A
BUSBAR		Standard length: 4 meters*, 4 conductors. Standard length: 4 meters*, 5 conductors. Conductor type.	TR60404CW TR60405CW Included in busbar code 10x1 - 10mm ²	TR60604CW TR60605CW Included in busbar code 10x1.5 - 15mm ²
JOINT BOX		Material: plastic. To connect two busbars.	TR6001W	
HANGER CLAMP		Material: plastic. Max support spacing: 133 m.	TR6002W	
END CAP		Material: steel. Max support spacing: 133 m.	TR6020	
FEED BOX		Material: plastic. Closes and protects the busbar end.	TR6006W	
IN-LINE FEED			TR6003A4W	
			TR6003A5W	
			TR6008A4W	
TROLLEY CURRENT COLLECTOR			TR6008A5W	
			TR6004	
			TR6005	

ITEM	PRODUCT	SPECIFICATION	40A	60A
TOWING ARM		To use to move the trolley current collector.	TR8557	
TOWING ARM BRACKET		Alternative product of TR8557 (with TR8510).	TR86007	
TOWING ARM		To use with TR6007 or TR6013.	TR8510	
DOUBLE TROLLEY SUPPORT		For utilization with two trolleys in order to have ampacity of 50A.	TR6013	
FIXED POINT		To fix the line to control thermal expansion, 1 for each line.	TR6014W	
TRANSFER GUIDE			TR6034A4W	
			TR6034A5W	
			TR6035A4W	
SPRING LOADED TOWING ARM			TR6035A5W	
			TR8538	
GASKET IP44		For transfer guide.	TR6012	

* Curved busbar available on request ONLY 4 conductors.

* Range (4 Pole): 40A, 60A, 70A, 100A and 140Amps are usually stock items.
* In Two types: Pre-mounted conductors (joint-type) and Continuous conductors (joint less type).