

Pendant stations











P03 Series pendant stations for small hoist applications

IP65 □











www.powermechengineering.com

www.powermechengineering.in

Single / Dual speed

P03		ENGRAVING	DESCRIPTION	CODE	WEIGHT gr	DIMENSIONS
	2 directions mechanically interlocked	  	For single speed motor control n° 1 emergency stop EN ISO 13850 mushroom Ø 30 turn to release with: n° 2 push buttons with 1 NO contact n° 2 push buttons with 2 NO contacts n° 2 push buttons with 3 NO contacts	P03.1 P03.2 P03.3	440 450 460	
						
			For 1kW single-phase motor control n° 1 emergency stop EN ISO 13850 mushroom Ø 30 turn to release with: n° 2 push buttons with 2 NO+1NC contacts	P03CD	460	
		  				

Code P03K, Enclosures in kit for contact blocks and operators, see codes to page 19
for assembly instructions see page 15

	  	For double-speeds motor control n° 1 emergency stop EN ISO 13850 mushroom Ø 30 turn to release with: n° 2 push buttons with 2 NO contacts	P03D2	460	
					
	  	For single-speed motor control n° 1 key switch Q-1 90° switching with: n° 1 push buttons with 1 NO contact n° 2 push buttons with 1 NO contact	P03CH	460	